# 船用网线 Marine Ethernet cable

HF Flame Oil Cold UV MUD

## CAT 6 AFL S/FTP 4PR 23AWG/1 SHF-MUD (GSWB)



## 应用 Application


符合 IEC 61156-5 标准的高性能海上 LAN 电缆，带宽高达 250 MHz。

High performance offshore LAN cable compliant with IEC 61156-5 category 6 standards bandwidths up to 250 MHz.

铜导体，发泡 PE 绝缘，铝箔对屏蔽，镀锡铜编织总屏蔽，SHF1 内护套，镀锌钢丝铠装，SHF-MUD 外护套。

BC conductor ,Foam PE insulation ,Foil screened pairs with an overall tinned copper braid ,SHF1 inner sheath, Galvanized steel wire armored ,SHF-MUD outer sheath.

## 结构 Construction




| | | |
|---|---|---|
| 导体 Conductor | 单根铜丝（23AWG/1） | Solid Bare copper wire（23AWG/1） |
| 绝缘 Insulation | 发泡 PE<br>颜色： 1、白/蓝，蓝 2、白/橙，橙<br>3、白/绿，绿 4、白/棕，棕 | Foam PE<br>Color：1、White/Blue，Blue 2、White/Orange，Orange<br>3、White/Green，Green 4、White/Brown，Brown |
| 线对屏蔽 Individual screen | 铝箔 | AL/Mylar |
| 总屏蔽 Overall screen | 镀锡铜编织，覆盖率≥60% | Tinned copper braiding, coverage≥60% |
| 内护套 Inner Sheath | SHF1 | SHF1 |
| 铠装 Armored | 镀锌钢丝铠装，覆盖率≥90% | Galvanized steel wire braiding, coverage≥90% |
| 外护套 Outer Sheath | SHF-MUD<br>颜色：灰色或定制<br>OD：11.5 ± 0.8mm | SHF-MUD<br>Color ：Grey or as customer's request<br>OD：11.5 ± 0.8mm |
| 印字 Marking | Hysin□MARINE□Cable□CAT6□AFL□S/FTP□4PR□23AWG/1□SHF-MUD□GSWB□IEC60332-3-22□NEK 606□****m□xxxxxx□WW/YY<br>注：□ 表示空格；****m 表示计米；xxxxxx 表示批号;WW/YY 表示周数/年份<br>Note：□ means blank；****m means meters；xxxxxx means batch number；WW/YY means week/year | |

## 电气性能 Electrical Characteristics（20℃）

| | | |
|---|---|---|
| 导体直流电阻 | Conductor DC resistance | ≤95 Ω/km |
| 电阻不平衡 | DC Resistance Unbalance | ≤2%（within a pair），≤5%（between pairs） |
| 特性阻抗 | Characteristic impedance | 100±10 Ω@100MHz |
| 介电强度 | Dielectric Strength | DC 1kV for 1min（conductor to conductor, conductor to screen） |
| 绝缘电阻 | Insulation Resistance | ≥5000MΩ.km（IEC 61156-5） |
| 电容不平衡 | Capacitance Unbalance（pair to ground） | ≤160pF/100m at 1kHz(IEC 61156-5) |
| 传输性能 | Transmission performance | IEC 61156-5 |

| Frequency<br>频率<br>MHz | ATT<br>dB/100m<br>Max.最大 | RL<br>dB<br>Min.最小 | NEXT<br>dB<br>Min.最小 | PSNEXT<br>dB<br>Min.最小 | ELFEXT<br>dB<br>Min.最小 | PSELFEXT<br>dB<br>Min.最小 |
|---|---|---|---|---|---|---|
| 4 | 3.83 | 23.0 | 66.3 | 63.3 | 56.0 | 53.0 |
| 8 | 5.37 | 24.5 | 61.8 | 58.8 | 49.9 | 46.9 |
| 10 | 6.00 | 25.0 | 60.3 | 57.3 | 48.0 | 45.0 |
| 16 | 7.61 | 25.0 | 57.2 | 54.2 | 43.9 | 40.9 |
| 20 | 8.53 | 25.0 | 55.8 | 52.8 | 42.0 | 39.0 |
| 25 | 9.57 | 24.3 | 54.3 | 51.3 | 40.0 | 37.0 |
| 31.25 | 10.75 | 23.6 | 52.9 | 49.9 | 38.1 | 35.1 |
| 62.5 | 15.48 | 21.5 | 48.4 | 45.4 | 32.1 | 29.1 |
| 100 | 19.92 | 20.1 | 45.3 | 42.3 | 28.0 | 25.0 |
| 200 | 29.14 | 18.0 | 40.8 | 37.8 | 22.0 | 19.0 |
| 250 | 33.02 | 17.3 | 39.3 | 36.3 | 20.0 | 17.0 |

## 其他性能 Other Characteristic

| | | |
|---|---|---|
| 工作温度 | Operating temperature | -40℃ to 90℃ |
| 安装温度 | Installation temperature | -20℃ to 60℃ |
| 卤酸气体 | Acid Gas Release Mounts | ≤5mg/g (IEC 60754-1) |
| 燃烧气体 PH 值 | Burning Occur Gas Acidity | PH≥4.3 (IEC 60754-2) |
| 燃烧气体导电率 | Burning Occur Gas conductivity | <10 μS/mm (IEC 60754-2) |
| 烟密度 | Smoke density | ≥60%（IEC 61034-2） |
| 阻燃性 | Flame resistance | IEC 60332-3-22, IEC 60332-1-2 |
| 耐油 | Oil resistance (SHF2) | IRM902, 100℃×24H |
| 耐泥浆 | MUD resistance (SHF-MUD) | NEK 606 |
| 抗紫外线 | UV resistance | UL1581 |
| 护套材料性能 | The jacket material performance | IEC 60092-360 |
| 最小弯曲半径 | Min.Bending radius | 15xOD(OD=cable diameter) |
| 重量 | Weight | 175±10 kg/km |

This cable meets RoHS requirements.

| Prepared by: J.Zhou | Checked by: CL.Wang | Approved by: SY.Xiang |
|---|---|---|